

CHRYSLER SMALL BLOCK ALUMINIUM HEAD SPECIFICATIONS – 318-340-360 ENGINES	
---	--

COMBUSTION CHAMBER VOLUME (CC)	65 cc
-----------------------------------	-------

INTAKE RUNNER VOLUME (CC)	176 cc
---------------------------	--------

EXHAUST RUNNER VOLUME	77 cc
-----------------------	-------

INTAKE VALVE DIAMETER (INCH)	2.020 inch
------------------------------	------------

EXHAUST VALVE DIAMETER (INCH)	1.60 inch
-------------------------------	-----------

VALVE GUIDES MATERIAL	MANGANESE BRONZE
-----------------------	---------------------

VALVE STEM DIAMETER	11/32 inch
---------------------	------------

MAXIMUM VALVE LIFT	0.575"
--------------------	--------

VALVE SPRING DIAMETER (INCH)	1.55 inch
------------------------------	-----------

VALVE STEM SEAL STYLE	VITON SEAL
-----------------------	------------

DECK THICKNESS (INCH)	5/8 INCH
-----------------------	----------

VALVE ANGLE	18 degrees
-------------	------------

EXHAUST PORT LOCATION	Stock
-----------------------	-------

SPARK PLUG	STRAIGHT
------------	----------

INTAKE PORT LOCATION	STOCK
----------------------	-------